





## Paging Horns

[SPT15A Horn Datasheet \(pdf\)](#)

[SPT30A Horn Datasheet \(pdf\)](#)

### Specifications

#### Features

- For noisy areas
- Indoor or outdoor
- All metal construction
- All purpose mounting bracket
- 15 or 30 watt horns

Ideal for applications where weatherproof construction is important. They include an adjustable all-purpose mounting bracket.

[\[Back\]](#)

---

## Speaker and Horn Specifications

Model	Volume Control Knob	Mounting	Frequency Response	70 Volt Transformer	Power Taps (watts)
S86T725PG8W Ceiling Speaker	No	Ceiling	50Hz to 12KHz	Yes	4, 2, 1, 1/2, 1/4, 1/8
WBS8T725V Wall Speaker	Yes	Wall	50Hz to 12KHz	Yes	4, 2, 1, 1/2, 1/4, 1/8
SPT15A Horn	No	Multi-purpose	275Hz to 14KHz	Yes	15, 7.5, 3.8, 1.8, 0.9
SPT30A Horn	No	Multi-purpose	225Hz to 14KHz	Yes	30, 15, 7.5, 3.7, 1.8

## **A RM-200RM Remote Paging Microphone**

### **TOA RM-200RM Remote Microphone**

The RM-200M Remote Microphone connects to the VM-3240VA, VM-3360VA, VM-2120 and VM-2240 for the purpose of making emergency(\*3)/general broadcast announcements.

#### **Specifications:**

- **Power Source:** 24 V DC (Operating range: 14 - 28 V DC)  
Power input jack: Non-polarity type  
Usable power input plug(\*2): Outer diameter  $\phi$ 5.5 mm, inner diameter  $\phi$ 2.1 mm, length 9.5 mm
- **Current Consumption:** 100 mA or less
- **Audio Output:** 0 dB(\*1), 600  $\Omega$ , balanced
- **Distortion:** 1% or less
- **Frequency Response:** 100 - 20,000 Hz
- **S/N Ratio:** 60 dB or more
- **Microphone:** Unidirectional electret condenser microphone
- **No. of Function Keys:** 13, Emergency key (covered), Talk key
- **Emergency Broadcast(\*3):** Activation of Emergency Broadcast (pre-recorded announcement or live microphone announcement) by Emergency Broadcast Switch
- **Volume Control:** Microphone volume control
- **Connection Cable and Connector:** Category 5 STP cable, RJ45 connector
- **Finish:** ABS resin, blueish gray (PANTONE 538 or its equivalent)
- **Dimensions:** 190 (W) ? 76.5 (H) ? 215 (D) mm (Gooseneck microphone excluded)
- **Weight:** 750 g
- **Accessory:** Link cable (3 m) ??1
- **Option:** Wall mounting bracket: WB-RM200

**Availability:** Ships in 3-4 business days.

**Shipping:** Can ship only within The Philippines